



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL: URD-SWEETBRIAR

SPECIFICATION & FEATURES

URD-SWEETBRIAR

This cable consists of several stranded, compressed 1350-H16/H26 aluminum wiring rated at 600V or less for direct burial use insulated with a cross-linked polyethylene. Conductor Material: AA 1350.

- ASTM B-230, B-231
- ASTM B-609, B-901
- UL Standard 854 requirement for USE-2
- ICEA S-105-692
- RoHS environmental conductive requirement



CERTIFICATIONS/WARRANTY

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

CONSTRUCTION

Voltage Rating 600V	Length 1000FT	Outside Diameter 0.512"(Phase),0.406"(Neutral)	Conductor Size 4/0-4/0-2/0
Strands 19/19	Resistance 0.274/0.436Ω/km @20C	Temperature Rating 90°C	Number Of Conductors 3

Insulation Material

Cross Linked Polyethylene

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



11675 SW TOM MACKIE BLVD. | PORT ST. LUCIE, FL 34987 | P: 772.878.4944 | WWW.RPP-USA.COM



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL:

ORDERING INFORMATION

Part Code	IMS Code
URD-SWEETBRIAR	0599-0340

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



11675 SW TOM MACKIE BLVD. | PORT ST. LUCIE, FL 34987 | P: 772.878.4944 | WWW.RPP-USA.COM