



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL: URD-BRENAU

SPECIFICATION & FEATURES

URD-BRENAU

This cable consists of several stranded, compressed 1350-H16/H26 aluminum wiring rated at 600V or less for direct burial use insulated with a cross-linked polyethylene. Conductor Material: AA 1350.

- ASTM B-230, B-231
- ASTM B-609, B-901
- UL Standard 854 requirement for USE-2
- ICEA S-105-692
- RoHS environmental conductive requirement



CERTIFICATIONS/WARRANTY

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

CONSTRUCTION

Voltage Rating

600V

Length

1000FT

Outside Diameter

0.362"(Phase),0.283"(Neutral)

Conductor Size

1/0-1/0-2

Strands

19/7

Resistance

0.550/0.875Ω/km @20C

Temperature Rating

90°C

Number Of Conductors

3

Insulation Material

Cross Linked Polyethylene

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



11675 SW TOM MACKIE BLVD. | PORT ST. LUCIE, FL 34987 | P: 772.878.4944 | WWW.RPP-USA.COM



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL:

ORDERING INFORMATION

Part Code	IMS Code
URD-BRENAU	0599-0352

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



11675 SW TOM MACKIE BLVD. | PORT ST. LUCIE, FL 34987 | P: 772.878.4944 | WWW.RPP-USA.COM