



| | |
|--------------|---------------|
| CONTRACTOR: | |
| PROJECT: | DATE: |
| PREPARED BY: | MODEL: XHHW-2 |

SPECIFICATION & FEATURES

With RPP XHHW-2 Wire being suitable for wet/dry locations, it can be used in a variety of applications including house building, conduit, feeders, and branch circuit wiring.

- 600/1000V rated
- AA8000 series aluminum
- XLPE insulation
- Wet/dry locations up to 90°C
- UL 44, ASTM B 800, ASTM B 801



CERTIFICATIONS/WARRANTY

Listing: UL listed, ASTM B 800 , ASTM B 801

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

CONSTRUCTION

| | | | |
|----------------------------------|---|---|---|
| Number of Conductors 1 | Voltage Rating 600/1000V rated | Length 1000' | Temperature Rating Wet/dry locations up to 90°C |
| Color Black | Core 8000 series aluminum compacted core | Insulation Material XLPE insulation | |

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



11675 SW TOM MACKIE BLVD. | PORT ST. LUCIE, FL 34987 | P: 772.878.4944 | WWW.RPP-USA.COM



| | |
|--------------|--------|
| CONTRACTOR: | |
| PROJECT: | DATE: |
| PREPARED BY: | MODEL: |

ORDERING INFORMATION

| Part Code | IMS Code | Conductor Size | Strands | Thickness | Diameter |
|-----------------------|-----------|----------------|---------|-----------|----------|
| XHHW-2-6-BLK-STR-AL | 0584-0355 | 6 | 7 | 45 | 0.262" |
| XHHW-2-4-BLK-STR-AL | 0584-0346 | 4 | 7 | 45 | 0.306" |
| XHHW-2-3-BLK-STR-AL | 0584-0364 | 3 | 7 | 45 | 0.386" |
| XHHW-2-2-BLK-STR-AL | 0584-0331 | 2 | 7 | 45 | 0.361" |
| XHHW-2-1/0-BLK-STR-AL | 0584-0334 | 1 / 0 | 18 | 55 | 0.449" |
| XHHW-2-2/0-BLK-STR-AL | 0584-0325 | 2 / 0 | 18 | 55 | 0.489" |
| XHHW-2-3/0-BLK-STR-AL | 0584-0349 | 3 / 0 | 18 | 55 | 0.536" |
| XHHW-2-4/0-BLK-STR-AL | 0584-0304 | 4 / 0 | 18 | 55 | 0.588" |
| XHHW-2-250-BLK-STR-AL | 0584-0322 | 250 | 35 | 65 | 0.653" |
| XHHW-2-300-BLK-STR-AL | 0584-0352 | 300 | 35 | 65 | 0.703" |
| XHHW-2-350-BLK-STR-AL | 0584-0337 | 350 | 35 | 65 | 0.749" |
| XHHW-2-400-BLK-STR-AL | 0584-0343 | 400 | 35 | 65 | 0.792" |
| XHHW-2-500-BLK-STR-AL | 0584-0319 | 500 | 35 | 65 | 0.869" |
| XHHW-2-600-BLK-STR-AL | 0584-0328 | 600 | 58 | 80 | 0.979" |
| XHHW-2-700-BLK-STR-AL | 0584-0361 | 700 | 58 | 80 | 1.04" |
| XHHW-2-750-BLK-STR-AL | 0584-0340 | 750 | 58 | 80 | 1.071" |
| XHHW-2-900-BLK-STR-AL | 0584-0358 | 900 | 58 | 80 | 1.162" |

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

