



MODEL :	TYPE
PROJECT :	
PREPARED BY :	DATE :

SERIES SPECIFICATIONS

Fire alarm cable is suitable for interconnection of electrical devices within a fire-protective signaling system. This wire is suitable for use in either dry or damp locations. It is made with solid copper conductors.



CONSTRUCTION

Wire Material

Annealed solid bare copper

Jacket Material

Red PVC

Insulation

PVC

Rating

UL (E464899) type FPLR, CL3R,CMR

Suggested Voltage Rating

300V

Operating Temperature

-20°C ~ 75°C

ORDERING INFORMATION

Part #	AWG Size	Nom. Dia. Insulation (mm)	Nom. Dia. Jacket (mm)	IMS Code
WC FPLR 18/2	18	1.52	3.8	0363-8079
WC FPLR 18/4	18	1.52	4.45	0363-8085
WC FPLR 16/2	16	1.8	4.35	0363-8073
WC FPLR 16/4	16	1.8	5.13	0363-8076
WC FPLR 14/2	14	2.3	5.33	0363-8070

No. of Conductor	Color
1	Black
2	Red
3	Brown
4	Blue

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

