



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

## SERIES SPECIFICATIONS

12/2 Landscape Cable, Low Voltage, Direct Burial, 500 Ft.  
 UV Resistant for outdoor use  
 Suitable for accent outdoor lighting, including landscape and security not exceeding 150V  
 Rated for underground burial use  
 Duplex flat construction for easy separation of conductors for installation



## CONSTRUCTION

Color Black	Data Rate 150V	Temperature Rating From -20°C to 60°C maximum
Conductor Material Copper	Shield Coverage N/A	Shield Material From -20°C to 60°C maximum
Jacket Flame Rate	Jacket Type PVC	

## ELECTRICAL SPECIFICATIONS

AWG 12	Conductors 2	Jacket Nom. Diameter N/A
Jacket Nom. Thickness 0.46 - 0.52	Wire Construction Stranded Flat	Conductor Construction 65 x 0.254
Resistance N/A		

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :	TYPE	
PROJECT :		
PREPARED BY :	DATE :	

## CERTIFICATIONS/WARRANTY

Listing  
UL listed Listed

Warranty  
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

## ORDERING INFORMATION

Part Number: LV 12/2 - 500

Box Qty : 500 Ft.

Weight (Lbs) : 0.0595

Carton Qty. : 500 Ft.

IMS Code : 0252-8799

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM