



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

14/2 Landscape Cable, Low Voltage, Direct Burial, 500 Ft.
 UV Resistant for outdoor use
 Suitable for accent outdoor lighting, including landscape and security not exceeding 150V
 Rated for underground burial use
 Duplex flat construction for easy separation of conductors for installation



CONSTRUCTION

Color
Black

Data Rate
150V

Temperature Rating
From -20°C to 60°C maximum

Conductor Material
Copper

Jacket Type
PVC

ELECTRICAL SPECIFICATIONS

AWG
14

Conductors
2

Conductor Construction
41x0.254

Insulation Nom. Thickness
0.46 - 0.52

Wire Construction
Stranded Flat

Resistance @ 20°C Max Ω/km
8.88

CERTIFICATIONS/WARRANTY

Listing
UL Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM



MODEL :		TYPE
PROJECT :		
PREPARED BY :		DATE :

ORDERING INFORMATION

Part Number: LV 14/2-100

Part Code	IMS Code	Color	Length	Package Type
LV 14/2-100	0373-5492	Black	100 Ft.	Pull Box
LV 14/2-500	0373-5495	Black	500 Ft.	Pull Box

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM